



CANOPY PERMIT ADDENDUM

Approval is subject to the following conditions:

GENERAL / BUILDING

1. All work shall comply with all applicable codes as adopted and amended by the Village of Glendale Heights.
 - 2006 International Building Code
 - 2006 International Fire Code
 - 2008 National Electric Code
 - Current Illinois Accessibility Code (1997)
 - 2010 ADA Standards for Accessible Design
 - Village of Glendale Heights Zoning Ordinance
2. Awnings and canopies shall be designed and constructed to withstand wind or other lateral loads and live loads as required by Chapter 16 of the International Building Code with due allowance for shape, open construction and similar features that relieve the pressures or loads. Structural members shall be protected to prevent deterioration. Awnings shall have frames of noncombustible material, fire-retardant-treated wood, wood of Type IV size, or 1-hour construction with combustible or noncombustible covers and shall be either fixed, retractable, folding or collapsible. (2006 IBC, 3105.3)
3. Canopies shall be constructed of a rigid framework with an approved covering that meets the fire propagation performance criteria of NFPA 701 or has a flame spread index not greater than 25 when tested in accordance with ASTM E 84. (2006 IBC, 3105.4)

ELECTRICAL

1. Upon completion of the canopy installation, field inspection shall be performed to ensure that adequate illumination of the path of egress is maintained. Where required, a photometric plan shall be prepared and submitted to the Village for review and approval by the _____ Fire Protection District. If necessary, a separate permit shall be required and additional lighting shall be provided.

FIRE

1. The project falls within the regulatory boundaries of the _____ Fire Protection District. The work of this permit is subject to their inspection and approval.

I hereby certify that I have read and understand all of the above regulations, and I agree to comply with all of the regulations contained herein.

Signature

Date

10/20/2015